MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

Product Name: TOTAL BATHROOM CLEANER

Product Number: 277

Product Type: AEROSOL

Supplier's Name: Terand Industries, Inc.

D.O.T. Hazard Class: CONSUMER COMMODITY · ORM-D

Supplier's Address: P.O. Box 9947, Ft. Lauderdale, FL 33310

Formula: Proprietary Date Prepared: 01/01/95

Emergency Phone: (800) 255-3924

Information Phone: (954) 974-5440

HMIS Rating (Based on Aerosol Conc.): 0-Minimal 1- Slight 2- Moderate

3- Serious 4- Extreme

HEALTH: 0 FIRE: 0 REACTIVITY: 0

Personal Protection: A

SECTION II · INGREDIENTS

CHEMICAL NAME CAS# %WT 313/Chem Skin Carcinogen PEL TWA/TLV Viable Bacteria Culture N/A 05-10 NO NO NO N/E N/E Liquified Petroleum Gas 68476-85-7 05-10 NO NO NO 1000 ppm 1000 ppm

SECTION III · PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only:

Boiling Point: ~212° F

pH: 9.0

Solubility In Water: Complete

Appearance/Odor: White Foam with Proprietary Good Earth Scent

Data Below Based On Total Contents: Vapor Pressure of can (psig @70°F): 55

Total VOC %: ~6.0%

Vapor Density(Air=1): >1

Specific Gravity (H2O=1)@70°F: 1.00

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (of Concentrate Only): None to Boiling(212° F - T.O.C)

Extinguishing Media: Foam, CO2, Dry Media

Flammability (as per USA Flame Projection Test): Non-Flammable Spray

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing. Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.

SECTION V · REACTIVITY DATA

Stability: Material Stable.

Hazardous Polymerization: Will not Occur.

Incompatibility: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxides.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F.

NFPA Code 30B Rating: Level 1 Aerosol.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged contact may cause irritation. Avoid all contact with open wounds.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

Ingestion: No effect if ingested in small amounts. Relative to other materials a single dose of this product is rarely toxic by ingestion. Irritation of the mouth, pharynx, esophagus and stomach can develop following ingestion.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

Protective Gloves: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made. Eye Protection: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstances. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.

> - DISTRIBUTED BY -NATIONAL AMERICAN SALTT 504-447-1434 800-821-3732 (LA)